



### Equipment Description

All Towers are skid mounted and fully packaged as standard. Stainless Steel Basins are standard and all units are shipped complete with weatherproof starter panel for easy, single point connection. Units are designed to easily be off-loaded with a forklift.

### Mechanical Connections

Inlet (Hot Water) 2 – 6" Dia., Victaulic

Outlet (Cold Water) 2 - 10" Dia., Victaulic

Make-up Water 2 – 2" Dia., MPT

Overflow 2 – 3" Dia. FPT

### Physical Data

Model Evapco AT-28-624-S

Length 24' 2"

Width 7' 10"

Max. Height 10' 6"

Design Flow Range 500 - 1,500 GPM

Operating Weight 15,600 lbs.

Shipping Weight 8,350 lbs.

### Electrical

Motor 2 x 25hp

Total HP/F.L. Amps 50hp /68a.

Phase/Hz/Volts 3/60/460

Enclosure TEFC

Fan F.L. Amps 34a.

Main Breaker 100a.

Basin Heaters 2 x 6000 watt

Fans Axial - V - Belt Drive

### Materials/Construction

Basin 304 Stainless Steel

Structure 304 Stainless & Hot Dip Galvanized Steel with Zinc Coating (G-235)

Drift Eliminators PVC

Mounting Brackets 304 Stainless Steel

Heat Transfer Media Honeycomb Sheet

Water Distribution PVC Header / ABS Nozzles

Supports 304 Stainless Steel

Varitech Equipment Company, Inc.  
1225 Veal Street  
Cedartown, Georgia 30125  
800.445.6085

[www.rentalcoolingtowers.com](http://www.rentalcoolingtowers.com)